



DATASHEET

of SAW Devices

SAW Resonator

Part Number: SXR304M250ATOE

Center Frequency: 304.250MHz

Package: DIP-TO39

- Package Dimensions
- Testing Environment
- Electrical Characteristics
- Frequency Characteristics

SAW Components	SAW Resonator
Part Number	SXR304M250ATOE



Revision Record

Revision Number	Date	Description
SXR304M250ATOE_Rev1.0	2023-05-10	Revision 1.0

1. Features

- 1-port SAW resonator
- Ceramic package for Surface Mounted Technology (SMT)
- Lead-free production and RoHS Compliant
- Electrostatic Sensitive Device(ESD)
- Moisture Sensitivity Level 2

2. Package Dimension(Unit: mm)



Pin No.	Function
1	Input
2	Output
3	Ground

Pin Configuration	
1	Input
2	Output
3	Ground


SAW Components

SAW Resonator

Part Number

SXR304M250ATOE

2. Measurement Circuit



3. Maximum Ratings

Rating		Value	Unit
RF Input Power	P	10	dBm
DC Voltage	V _{DC}	10	V
Operating Temperature Range	T _A	-40 ~ +85	°C
Storage Temperature Range	T _{stg}	-45 ~ +85	°C
ESD Voltage(MM)	V _{MM}	50	V
ESD Voltage(HBM)	V _{HBM}	175	V

4. Electrical Specification

Item	Frequency Range	Characteristics			
		min.	typ. ¹	max.	Unit
Center Frequency	Absolute Frequency	304.175	304.250	304.325	MHz
	Tolerance from 304.250MHz	-	±75	-	kHz
Insertion Loss	Min.	-	1.5	2.2	dB
Anti-resonance	-	24	25	-	dB

1. Typical value at 25±2deg.C

5. Typical Frequency Characteristic

